$\mathsf{VKP80}$ 80MM RECEIPT/TICKET PRINTER

MAIN FEATURES

- 200dpi best printing quality
- Paper width from 50 to 82.5 mm
- . Paper thickness from 60 to 110 g/m²
- Speed > of 250 mm/sec
- .
- Ejecting & Retracting (speed > of 1000 mm/s) Paper roll (diameter 250mm) and fan-fold (450 tickets) .
- High reliable and sturdy
- RŠ232 and USB 2.0 full speed interface
- Barcodes 1D&2D: UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, • PDF417, DATAMATRIX, AZTEC, QRCODE
- TrueType fonts supported and "drag&drop" logos and graphics
- Highly reliable cutter: > of 1.000.000 cuts
- MŤBÉ > 150.000 hours
- . Sensors: paper end (ticket presence), paper out, open printer cover, near paper end on external paper roll holder, printing head temperature
 - VeryNotch : mobile notch/black mark sensor, non thermal side Optional TopNotch

EXCLUSIVE FEATURES

- The most compact kiosk printer with small footprint: 116x143x76 mm
- Flexible: separate roll holder in different position with hergonomic paper loading from the right or left side, suiting all kiosk designs Available connectors on the left side (standard) or back side (optional) High performance 96MHz microprocessor

- Anti-jamming system (patented) 8MB RAM + 3MB Flash memory Autoclean system Automatic ticket ejecting & retractring back, with also retracting function w/o presenting paper (patented)

1108dyn

- Illuminated paper bezel

- Hot swap function: it is possible to remove the printer from the kiosk w/o powering it off Micro SD card optional to expand the memory for logos, fonts, etc VeriNotch and optional TopNotch special sensors Low power mode (EcoGreen) Print head self-diagnostic function: it is possible to get the percentage of not working dots

MOST COMMON APPLICATIONS

- Self-service kiosks
 ATMs & Banking machine
- Gaming machine
 Couponing
- Parking payment terminal
- Vending machine
 Control access

SOFTWARE FEATURES

- Status Monitor DLL Full Windows Status Monitor Driver Self-installing Driver for Win2000/XP/Vista /7 (+64bit support) Linux Driver TrueType fonts supported and European, International and Russian fonts directly on board; GB2312, BIG5 and 18030 Chinese fonts optional Logos dynamic management: large number of logos and graphics can be loaded with a simple drag and drop, up to a maximum of 2MB



OPTIONS


- Micro SD Card to expand the memory for logos, font etc up to 2GB TOP NOTCH sensor: it reads notch or hole in thermal upper side, both on right or left edges

PRINT&READ SYSTEM (patented)



NO LONGER A PRINTER **BUT A PRINTING & READING SYSTEM!**

AVAILABLE VERSIONS Serial+USB 24V side connector
 Serial+USB 24V back connector



Xecogreen

