

# Interactive Touch Screen Digital Signage Display

## » MODEL :

- ① BSS-SH4701T
- ② BSS-SV4201T
- ③ BSS-SV4701T



①



②



③

## » SPECIFICATIONS

Resolution	1920*1080
Contrast	1500:1
Brightness	500cd/m2
Storage Capacity	Built-in hard disk, 160 G
Viewing Angle	L/R/U/D 178° /178° /178° /178°
Working Environment	-20°C ~ 40°C
Power Supply	AC 90V~ 264V 50/60Hz
Power of Unit	250 W ( ② ) , 300 W ( ①/③ )

## » APPEARANCE

### Aluminium Frame

### Tempered Glass Surface

**Overall Dimensions :** 1143mm x 639mm x 183mm ( ① )  
1750mm x 632mm x 78mm ( ③ )  
1800mm x 695mm x 78mm ( ② )

## » MAIN FUNCTIONS

- Full HD 1920\*1080, LCD screen, support display models of 16:9, 9:16 (Horizontal/Vertical) etc.
- Multi groups of on/off time schedule could be setted remotely and control the display through internet.
- Interactive optical multi points touch functions, touch in two points simulataneously.
- Compatible multimedia file formats : MPEG 1/2/4, AVI, RM, WMV, DAT, JPEG, BMP, PPT, WORD, EXCEL, TXT, MP3, RMVB, SWF etc.
- Rolling titles in English and Chinese version are available, various display models for titles (fonts and colors of letters, background colors, the relative attributes of rolling directions in horizontal or vertical could be adjusted).
- Support media contents like videos, pictures, flashes etc.
- Support uploading files through Wifi and cable network.
- Intelligent operating system, easy and fast operation.
- Support displaying in dual screens, play different video files and audio contents in these two screens.