

CHEXPRESS® CX30



- Fast and Quiet Scanning
- Intuitive Design
- Small Footprint
- Exceptional Image Quality
- Ultraviolet Image Capture

Simple. Affordable. Durable. Proven.

The award-winning CheXpress CX30 is the only bank-quality check scanner offered at a small business price. This stylish and quiet single-feed scanner is the perfect device for lower volume check capture environments.

Worry-Free Reliability

Our scanners are engineered to last. The CX30 will process over a million items during its life, which is the highest duty cycle of any scanner in its class.

The Ultimate in Low Maintenance

Maximize productivity and avoid hardware headaches. The CX30's simple transport design means minimal user maintenance is required.

Here, There, Anywhere

We know desktop real estate is at a premium. The CX30'seconomical footprint and flexible cable management system means you won't have an issue finding it a home in your workspace.

Pass Through Feed Option

Users can choose between "scan and return" or "pass through" scan modes. With "pass through", scanned items follow a straight paper path and exit through the rear of the scanner. Ideal for kiosks and other selfservice settings.

Extremely Fast, Remarkably Quiet

At a rated speed of one second per scan the CX30 makes quick work of any deposit. Concerned about noise? Don't be. The CX30 is remarkably quiet and suited for any work environment.

Image and MICR Quality is Everything

Featuring high performance front and rear image cameras with dual pass MICR read-head capability, the CX30 is truly in a class of its own. With our special document handling technologies, even the most challenging money orders and checks written with gel pen ink are a snap to process.

Encrypted Card Reader

The CX30 becomes a complete merchant check imaging and credit card payment processing machine with the addition of the optional DockXpress encrypted card reader. Designed to fit underneath any CX30 scanner, the DockXpress provides the strongest security for your credit and debit card transactions by encrypting sensitive data as soon as the card is swiped.

PRODUCTS SPECIFICATIONS

Camera Specs (Scanning Method)

Concurrent Two-Sided Duplex Resolution: 300 dpi (850 Pixel Linear Array) Light Source: Tri-Color LEDs Optional Front Ultraviolet Camera

Supported Operating Systems

Windows® XP, Windows Vista® (32/64 bit), Windows 7® (32/64 bit), Windows 8® (32/64 bit), Windows 10® (32/64 bit)

Electrical

Power Consumption: 24 Watts Input Voltage: 100 to 240 VAC, 50/60 Hz Separate Standard Power Supply: Auto sensing for voltage

Standard Warranty

1 year warranty

Environmental

Operating Temperature: 60° - 90° F (15° - 32° C) Operating Humidity: 35 - 85% non-condensing

Certifications

Safety: UL, cUL, CE FCC: Class B (Industrial, Business or Home) EMC: IEC CE Efficiency: CEC V 115V - Power Supply RoHS Compliant

Document Handling

Entry Pocket: 1 item at a time Exit Pocket: 5 items if Pass Through mode is enabled Document Height: 2.12" - 4.25" (54 - 108 mm) Image Capture Height: Up to 4.177" (106 mm) Document Length: 3.19" - 8.98" (81 - 228 mm) Document Weight: 16 - 28 lb. bond (60 - 105 gsm) Document Thickness: 0.0032" - 0.0058" (0.081 - 0.147 mm)

Printer Option

Single line inkjet printer with user replaceable cartridge

Franker Option User replaceable red ink stamp

MICR Recognition

(Magnetic Ink Character Recognition) for E13B (North America) and CMC7 (Europe) Optical Character Recognition to enhance MICR Read, further enhanced using DCC's Best Read[™] API function

Connectivity

Mini-B USB 2.0 cable and power supply included

Size

H: 7.47" (18.97 cm) W: 3.92" (9.96 cm) L: 9.38" (23.83 cm) Weight: 3.95 lbs. (1.8 kg)

 Business Smart Solutions Pty. Ltd.

 ② Unit 7/7-29, Bridge Road, Stanmore, NSW 2048, AUSTRALIA

 ● +61(2) 9516 2280
 ● +61(2) 9516 2290

 ● info@bss.com.au
 ♥ www.bss.com.au

© 2015 Business Smart Solutions. All products, images and brand names are trademark and owned by respective company and are used for descriptive purposes only. They are neither affiliated with, endorse or sponsor the use of this product. All specifications are subject to change for improvement purposes with prior notice.