

FB-30

Cheque scanner




The FB-30 is a very compact cheque scanner, handling a full range of documents for the financial industry. The FB-30 has the ability to read MICR (E-13B/CMC7), to endorse and to capture both front and rear images at a rate of up to 85 documents per minute. This innovative scanner provides the ability to enable distributed processing in your organisation instantly.

- Processing Speed up to 85 DPM (standard 6.7 inches document)
- Auto hopper / single stacker capacity - max 100 sheets
- MICR reading (CMC7/E13B)
- Ink-jet printer for rear endorsement
- High quality colour, greyscale and black and white 300 dpi images
- Single feed for plastic non-embossed card scanning (ID, license card)
- UV image scanning (option)
- Ultrasonic double feed detection for special paper (option)
- PC interface – image data and controls via USB 2.0
- Operating system – Windows XP / Vista / 7 / 8

Type (options)	Included features
FB-30	Standard unit
FB-30 S	With Ultrasonic double feed detection
FB-30 U	With UV image scanning

UV image sample



FB-30

Technical Information

Document feeder	Type	Auto hopper
	Capacity	100 documents (with 0.116mm thickness)
	Double feed detection	IR sensor <Ultrasonic sensor (option)>
MICR reader	Font read	E13B, CMC7
	Number of characters	65 characters or less
	Recognition rate	Greater than 99%
Endorser	Print head type	Ink jet 12 pin HP C6602A
Image scanner	Capture module	Contact image sensor
	Capture side	Front and rear
	Representation	8 bit grey / 24 bit colour (Jpeg or BMP)
		B/W (Tiff with G4 compression)
	Resolution	200, 240, 300 dpi
	UV image (option)	8 bit grey UV image with 200 dpi
	Scanning area (H x W)	108 x 235mm
Pocket	Capacity	100 documents (1 pocket stacker)
Single feeder	Single feed scan	Plastic ID card single feed (non embossing) or single document feed
Processing speed	8 bit grey	85 DPM
	24 bit colour	50 DPM
	8 bit grey with UV	75 DPM
Document specifications	Length	85mm – 235mm
	Height	70mm – 120mm
	Thickness	0.096mm – 0.156mm
System requirements	Operating system	Windows XP / Vista / 7 / 8
PC interface		USB 2.0
Dimensions (W x D x H)		335-405 x 148 x 188mm
Weight		2.6kg (AC adapter not included)
Power		24V DC adapter (100-240V, 50/60Hz)

*Specifications and design are subject to change without notice.

*Please carefully read the instruction manual to ensure correct equipment usage



Business Smart Solutions Pty. Ltd.

• Unit 7/7-29, Bridge Road, Stanmore, NSW 2048, AUSTRALIA
 • +61 (2) 9516 2280 • +61 (2) 9516 2290
 • info@bss.com.au • www.bss.com.au

7/7-29 Bridge Road, Stanmore, NSW 2048, AUSTRALIA Phone: +61 (2) 9516 2280 Fax: +61 (2) 9516 2290 info@bss.com.au www.bss.com.au

©2014 Business Smart Solutions. All products, images and brand names are trademark and owned by respective company and are used for descriptive purposes only. They are neither affiliated with, endorse or sponsor the use of this product. All specifications are subject to change for improvement purposes without prior notice.